



NASE

2-Tool Nano Rework Station

This Plug & Play Guide corresponds to the following references:

Ref.

NASE-9C (100 V)
NASE-1C (120 V)
NASE-2C (230 V)

Station

More Information at the
product web page



Video Guide

Watch the
product video



Packing List

The following items are included according purchased station reference:



NAE
2-Tool Nano Control Unit 1 unit
 Ref. NAE-9C (100 V)
 Ref. NAE-1C (120 V)
 Ref. NAE-2C (230 V)



AN115
Adjustable Nano Tweezers 1 unit
 Ref. AN115-A



NT115
Nano Handle 1 unit
 Ref. NT115-A



Ref. 0020952 includes:
 Ref. C115-101 x1
 C115-103 x1
 C115-107 x1
 C115-112 x1

Ref. 0020953 includes:
 Ref. C115-105 x2
 C115-113 x2



Cartridge
Dispenser Case 2 units
 Ref. 0020952 / Ref. 0020953


P405
Pedal 1 unit
 Ref. P-405

Installation


NAE
 2-Tool Nano Control Unit



Power Cord
 Supplied in NAE Control Unit



Installation



Specifications

NASE

2-Tool Nano Rework Station

Ref. **NASE-9C** (100 V) 50/60 Hz. Input fuse: 0.5 A. Output: 8.5 V.

Ref. **NASE-1C** (120 V) 50/60 Hz. Input fuse: 0.5 A. Output: 8.5 V.

Ref. **NASE-2C** (230 V) 50/60 Hz. Input fuse: 0.2 A. Output: 8.5 V.

- Package Dimensions / Weight: 280 x 280 x 164 mm / 2.99 kg
(L x H x W) 11.02 x 11.02 x 6.46 in / 6.59 lb

Complies with CE standards.
ESD safe.

JBC

Warranty

Information regarding the warranty of each product can be found on the final page of its instruction manual.



This product should not be thrown in the garbage.

In accordance with the European directive 2012/19/EU, electronic equipment at the end of its life must be collected and returned to an authorized recycling facility.